



# YORK® Residential products

For over 140 years, YORK® heating and air conditioning products have been trusted in the world's most prestigious buildings. That same commitment to strength, durability and innovation can be found in every residential unit we build. We are raising the bar on the quality of design, engineering and assembly to ensure our YORK home comfort products deliver performance, efficiency and reliability you can trust. With a complete line of YORK products to choose from, there is a system perfectly suited to provide optimal comfort, exceptional energy savings and lasting performance for every family.



# Split system air conditioners

Upfront Unit Cost	\$				\$\$\$\$	
Model(s)*	YC2E (Southern US); YC2D (Northern US and Canada)	YC2F	HMCG2 (Side discharge)	YXT (Affinity)	YXV (Affinity)	
Tonnage Range	1.5-5 Tons	1.5-5 Tons	2.5 Tons	2-5	Tons	
Efficiency	13.4 SEER2 (YC2D) 14.3 SEER2 (YC2E)	Up to 17.5 SEER2	Up to 18.5 SEER2	Up to 18.25 SEER2	Up to 20 SEER2	
Compressor Types	Single-stage	Single-stage (1.5-3 Tons) Two-stage (3.5-5 Tons)	Modulating compressor	Two-stage	Variable capacity	
Thermostat	Con	ventional		Conventional and communicating		
Comfort Technology				for enhanced humidity cont display for efficient diagno	ns with premium indoor units rrol. Easy-to-read digital LCD sis and servicing. Integrated ring for simple installations	
Additional Features	MicroChannel coil			Tube-ii	n-fin coil	
Sound	As low as 73 dBA	As low as 73 dBA	As low as 54 dBA	As low as 68 dBA	As low as 68 dBA	
Warranties <sup>†</sup>	10-Year Compres	ssor Limited Warrant	у	Lifetime Compressor Limited Warranty		
Harrancies		10-Y	ear Parts Limite	ed Warranty		

\* Single- and three-phase models available † For full warranty information, see back cover



# Split system heat pumps

Upfront Unit Cost	\$				\$\$\$\$	
Model(s)*	YH2E	YH2F	HMH7	YZT (Affinity)	YZV (Affinity)	
Tonnage Range	1.5-5 T	ons		2-5 Tons		
Efficiency	14.3 SEER2/7.5 HSPF2	SEER2/7.5 HSPF2 15.2 SEER2 16+ SEER2 8.1 HSPF2 8.1 HSPF2		18+ SEER2 8.1 HSPF2	19+ SEER2 9.0 HSPF2	
Compressor Types		Single-stage (1.5 Tons) Modulating Two-stage (2-5 Tons)			Variable capacity	
Thermostat	Conventional			Communicating or conventional	Communicating	
Comfort Technology			indoor units for enl Easy-to-read digita diagnosis and servic	logy aligns with premium nanced humidity control. I LCD display for efficient ing. Integrated refrigerant g for simple installations		
Additional Features	Tube-in-fin coil / 1,000-hour powder paint / Extruded louver coil guard / Demand defrost					
Sound	As low as 73 dBA	As low as 72 dBA	As low as 68dBA As low as Swept wing fan, composite base pan 54 dBA and factory-installed sound blanket for reduced sound			
Warranties <sup>†</sup>	10-Year	Compressor Limited War	ranty	Lifetime Compressor Limited Warranty		
Warrances		10-Y	ear Parts Limited Warrant		no phase models available (VIJE)	

\* Three-phase models available (YH2E) † For full warranty information, see back cover



# Packaged cooling and heating units

Model(s)	PCE4, PCG4 PCE6, PCG6					
Tonnage Range	2-5 Tons					
Efficiency	13.4 SEER2/ 81% AFUE (PCG4)	15.2 SEER2/ 81% AFUE (PCG6)				
Thermostat	Conventional 24v thermostats					
Phase	Single- and three-phase					
Warranties†	Lifetime Heat Exchanger Limited Warranty** (PCG6, PCG4) 10-Year Compressor Limited Warranty 10-Year Parts Limited Warranty					

## Packaged heat pumps

Model(s)	PHE4, PHG4 PHE6, PHG6					
Tonnage Range	2-5 Tons					
Efficiency	13.4 SEER2/ 6.7 HSPF2 81% AFUE (PHG4)	15.2 SEER2/ 7.2 HSPF2 81% AFUE (PHG6)				
Thermostat	Conventional 24v thermostats					
Phase	Single- and three-phase*					
Warranties <sup>†</sup>	Lifetime Heat Exchanger Limited Warranty** (PHG6, PHG4) 10-Year Compressor Limited Warranty 10-Year Parts Limited Warranty					

\* PHG4 and PHG6 are available in single-phase models only
\*\* 20-Year Heat Exchanger Limited Warranty on Ultra-Low NOx models
† For full warranty information, see back cover



## Furnaces

Upfront Unit Cost	\$			\$\$\$\$	\$			\$\$\$\$
Model(s)	TM8E (Ultra-Low NOx TL8E)	TM8Y	TM8V (Affinity)	YPLC (Affinity)	TM9E (Ultra-Low NOx TL9E)	TM9Y	TM9V (Affinity)	YP9C (Affinity)
Blower Motor		iciency ECM, -speed motor	High-efficiency ECM, constant CFM, variable-speed motor		Standard-efficiency ECM, discrete multi-speed motor		High-efficiency ECM, constant CFM, variable-speed motor	
Heating Stages	Single-stage	Two-stage	Two-stage	Variable speed	Single-stage	Two-stage	Two-stage	Variable speed
Available Heating Sizes	40-130 MBH (60-100 MBH ULNOx)	40-120 MBH	60-120 MBH	60-120 MBH	26-120 MBH (60-100 MBH ULNOx)	40-120 MBH	40-120 MBH	60-120 MBH
Controls/ Communication	Conventiona	l thermostat	Conventional or	communicating	Conventiona	al thermostat	Conventional or	communicating
Gas Burner Efficiency*	80% AFUE	80% AFUE	80% AFUE	80% AFUE	95% AFUE	96% AFUE	96% AFUE	98% AFUE
Heat Exchanger	eat Exchanger Non-condensing				Conde	ensing		

Heat Exchanger	Non-condensing	Condensing

Comfort Technology	Blower fi	ne-tuning	Premium variable-speed ECMs contain blower fine-tuning technology for Blower fine-tuning customized comfort based on geographic region		ECMs contain blower fine-tuning technology for Blower fine-tuning fine-tuning customized comfort based on		ECMs contain blower fine-tuning technology for customized comfort based on ECMs contain blower fine-tuning technology for customized comfort based on comfort b		tain blower logy for customized
Sound	Good	Good	Better	Best	Good	Good	Better	Best	
Warranties†	Limited V	at Exchanger Varranty** arts Limited	Lifetime Heat Exchanger 10-Year Parts Limited		Lifetime Heat Exchanger Limited Warranty** 10-Year Parts Limited			at Exchanger arts Limited	

<sup>\*</sup> Minimum efficiency ratings available in your area may vary as dictated by regional standards

\*\* 20-Year Heat Exchanger Limited Warranty on Ultra-Low NOx models

† For full warranty information, see back cover



## Air handlers

Upfront Unit Cost	\$		\$\$\$\$			
Model(s)	JHET, JMET	JHET, JMET JHVT, JMVT (Affinity)				
Tonnage Range	1.5-5 Tons	1.5-5 Tons 1.5-5 Tons				
Motor	High-efficiency, multi-speed motor (AE, ME) standard-efficiency, multi-speed motor (AP)	High-efficiency, multi-speed motor (AE, ME) standard-efficiency, multi-speed motor (AP)  High-efficiency, constant CFM motor				
Position	Multi-position*					
Thermostat	Conventional	Conventional Communicating or conventional				
Pairs With		Air conditioner/Heat pump				
Additional Features	MaxAlloy Coil™ Factory-installed TXV Less than 2% air leakage when tested at 1.0" ESP  MaxAlloy Coil™ Less than 2% air leakage when tested at 1.0" ESP					
Warranties <sup>†</sup>	10-Year Parts Limited Warranty					
			* No additional accessories or kits require			

\* No additional accessories or kits required † For full warranty information, see back cover



## Indoor evaporator coils

XAH, XAF	XAU	XAM
1.5-5 Tons     'A' coil design     Full-cased, horizontal configuration     MaxAlloy™ coil     AC and HP     Bolt-on TXV kits available	1.5-5 Tons     'A' coil design     Uncased, upflow/downflow     MaxAlloy™ coil     AC and HP     Bolt-on TXV kits available	1.5-5 Tons     'A' coil design     Full-cased; multi-position     MaxAlloy™ coil     AC and HP     Factory-installed EEV     Compatible with variable capacity units

Even-flow distributor design distributes refrigerant equally between coil circuits ensuring greater control and more consistent distribution of refrigerant.



## Indoor air quality products

All indoor air quality products come with a 5-Year Parts Limited Warranty.

Heat	rec	overy	, ve	ntilat	or/
eners	v r	ecov	erv	venti	lato

- · Optional defrost package
- · Five speeds for specific demands
- 160 and 220 CFM options
- 59-66 Sensible Recovery

## Hybrid electronic air cleaners • Un to MERV 16

- Up to 2,000 CFM
- · High efficiency with a low pressure drop
- No washing or vacuuming required

#### Media air cleaners

pressure drop

- · Up to MERV 13/Up to 2,000 CFM
- Easy-to-replace media filterHigh efficiency with a low

### Ultraviolet air treatment systems

- · Kill up to 99 percent of mold spore growth
- Indicator light for functionality and light bulb replacement
- Offered in single- and dual-lightbulb options
- 10" to 24" accordion section for installation flexibility

#### Whole-house humidifiers

- · Fan-powered evaporative, bypass evaporative and steam humidifiers
- · 12-18 gallon moisture delivery per day on evaporative models;
- up to 23.3 gallons on steam model

  Manual humidistat included
- · Easily mounts to the return ductwork
- · Nearly silent operation
- · Optional automatic humidifier controls available for fan-powered model

#### Whole-house dehumidifiers

- Integrates with indoor unit to remove excess moisture in the living space
- · 70, 95 and 130 pints per day
- Easy to maintain no need to empty messy water trays



#### Thermostats and controls

	Hx3 Communicating Zoning*	Hx3 Touchscreen Thermostat	Hx Touchscreen Thermostat	Higher Efficiency	Standard Efficiency		
Connectivity	Communicating	Conventional	or communicating	Conv	inventional		
Display	4.3" capacitive touc	chscreen	2.8" capacitive touchscreen	Backlit digital			
Control	Wi-Fi with	consumer and dealer	apps				
Access	Amazon Alexa-en	abled and Apple Watch	compatible				
Programmability	Programmable	Programmable Android NFC programmable			Programmable		
Diagnostics	System diagn	ostics for easy troubles	hooting	UV servi	ce indicator		
Special Features	Automatic system configuration - Plug-and-play, control for up to eight zones	Auto-humidity control, pre-set modes, remote dealer monitoring and adjustment with homeowner permission		Dual fuel operation, multi-stage, up to three heat and two cool stages, outdoor sensor capabilities	Battery or system powered, single- or multi-stage, up to two heat and two cool stages		
Warranty <sup>†</sup>		5-Year Limit	ed Warranty		1-Year Limited Warranty		

\* Dealer Design Award † For full warranty information, see below

To receive the extended 10-year parts warranty or premium system warranty for qualifying units, you must register online at www.upgproductregistration.com. Registration must be completed within 90 days of installation or 90 days of the closing date for new home construction. Failure to register online within 90 days results in a standard 5-year parts warranty. Failure to return the registration card does not affect rights under the standard warranty.



### Choose your controls with premium equipment

Our enhanced YORK Affinity premium equipment now gives you the power to choose your controls. You still get optimized performance using our own advanced Hx and Hx3 thermostats. However, our YORK premium variable capacity systems are now compatible with your choice of preferred controls and smart home devices, thanks to our new Universal Adapter.



Models listed with the ENERGY STAR logo meet the requirements for energy efficiency.



2021 Bronze Award winner: YORK Hx3 Communicating Zoning System.



This award recognizes products that are at the forefront of HVACR. The YORK TL9E Furnace won the 2020 AHR Expo Innovation Award in the Heating category.



YORK Heating and Cooling products have been awarded the Good Housekeeping Seal of Approval.



Through its sponsorship of the Building Homes for Heroes® program, Johnson Controls, along with YORK distributors and independent contractors nationwide, donated quality heating and cooling systems to injured veterans from the Iraq and Afghanistan wars. Since 2014, YORK has proudly helped make these gifted, mortgage-free homes comfortable for our injured heroes.



We are all about quality and it starts with a 2-Year Parts Warranty for all genuine YORK parts. Each genuine part is engineered, built to specification and tested to perform reliably in all of our equipment.

